



# Motorola V276 Small LCD Display Screen Replacement

Written By: Cecilia



## INTRODUCTION

Replacing a cracked or malfunctioning LCD display screen.

---

### TOOLS:

- [iFixit Opening Tools](#) (1)
  - [T6 Torx Screwdriver](#) (1)
  - [Spudger](#) (1)
-

## Step 1 — Front panel/ Screen Logic Board



- Using the plastic opening tool, pry off the top faceplate.
- Place the tool in the small crack that runs along the side of the phone and pry.


## Step 2



- Using the T6 Torx Screwdriver remove all 4 small screws.




### Step 3




- Remove silver plate from phone.

### Step 4



- Using the spudger remove the plastic camera casing

## Step 5




- Using the iPod Opening Tool remove the yellow flex cable from the green logic board.

## Step 6




- Use Spudger or hands to detach flex cable from front screen logic board

## Step 7 — Small LCD Display Screen



- Using the plastic opening tool, lift the small black flap to unlock the screen from the logic board.


## Step 8



- Using your fingers, carefully pull out the small LCD display screen.



## Step 9



- Remove the small LCD display screen completely from the green logic board.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-08 05:40:42 PM.